# LC-LC 62.5/125µm OM1 MM Duplex Fiber Optic Jumper



## **Package Includes**

A. LC-LC 62.5/125μm OM1 MM Duplex Fiber Jumper, **1 Piece** 

### **Features and Benefits**

- Made from OFNR riser rated cables, exceeding industry requirements
- Used with ICC fiber optic products
- Available in 1, 2, 3, 5, 7, and 10 meters
- Dust caps included
- 100% factory tested

Part No: ICFOJ1M3XX Rev: B

Page 1 of 2





#### **Product Specification**

### NOTE: UNLESS OTHERWISE SPECIFIED

#### 1. Cable:

A. Color: Orange

B. Fiber Counts: 2 Fiber Zipcord

C. Fiber Type: Multimode 62.5/125µm

D. Attenuation: 2.9/0.6 dB/km @ 850/1300 nm E. Bandwidth: 220 MHz.km EMB @ 850 nm

F. Cable Data:

• Cable diameter: .079 in (2.0mm)

Weight: 12 lbs./kft
Bend radius: 1.2" MIN
Loading: 135 lbs. MAX
Impact cycle: 1500

#### 2. LC Connector:

A. Ferrule: Zirconia

B. Insertion Loss: 0.2 dB Typical, 0.3 dB MAX

C. Reflection: N/A

3. Compliance:

A. ANSI/TIA-568-C.3

4. Length XX: 01, 02, 03, 05, 07, & 10

ITEM NUMBER	L (LENGTH)
ICFOJ1M301	1 METER ± 10 CM
ICFOJ1M302	2 METER ± 10 CM
ICFOJ1M303	3 METER ± 10 CM
ICFOJ1M305	5 METER ± 10 CM
ICFOJ1M307	7 METER ± 10 CM
ICFOJ1M310	10 METER ± 10 CM

Part No: ICFOJ1M3XX Rev: B

Page 2 of 2

icc.com I cs@icc.com

