48-Port 8P2C Female Telco Patch Panel

Package Includes

A. 48-Port 8P2C Telco Patch Panel, 1 pc B. #12-24 x 5/8" Pan Head, Pilot Point Machine Screw, 8 pcs



Features and Benefits

- Rack mounted 8-position 2-conductor Telco patch panel provides voice connectivity applications
- Integrated with two female 50-pin Telco connectors
- Designed to fit all standard 19" racks and cabinets
- 2 rack mount spaces (RMS)
- Country Of Origin: Taiwan
- **TAA Compliant**



Rev: A Page 1 of 2











Specifications









| WIRING C | | | W |
|--------------------|--------------|--------------------|--|
| PORT NO. | TELCO | USOC | PC |
| | 50 PIN 26 | RJ-45, 2-WIRE 5 | l |
| PORT 1 | 1 | 4 5 | l LP |
| PORT 2 | 27 | | l P |
| | 2 28 | 5 | l |
| PORT 3 | 3 | 4 | l LP |
| PORT 4 | 29 4 | 5 | _P |
| PORT 5 | 30 | 5 | l |
| | 5 | 4 | L P |
| PORT 6 | 31 6 | 5 | P |
| | 32 | 5 | _P |
| PORT 7 | 7 | 4 | l L |
| PORT 8 | 33 8 | 5 | P |
| PORT 9 | 34 | 5 | |
| PURI 9 | 9 | 4 5 | <u> </u> |
| PORT 10 | 35 10 | 4 | P |
| PORT 11 | 36 | 5 | - |
| FORTII | 11 37 | <u>4</u> 5 | 1 1 |
| PORT 12 | 12 | 4 | P |
| PORT 13 | 38 | 5 | 1 6 |
| | 13 39 | 5 | l H |
| PORT 14 | 14 | 4 | P |
| PORT 15 | 40 | 5 | 1 6 |
| | 15 41 | 5 | l H |
| PORT 16 | 16 | 4 | P |
| PORT 17 | 42 | 5 | 1 6 |
| | 17 43 | - 4 5 | ΙH |
| PORT 18 | 18 | 4 | P |
| PORT 19 | 44 | 5 | F |
| PORT 20 | 19 45 | 5 | l |
| | 20 | 4 | P |
| PORT 21 | 46 | 5 | P |
| PORT 22 | 21 47 | 4 5 | l |
| | 22 | 4 | P |
| PORT 23 PORT 24 | 48 | 5 | P |
| | 23 49 | 4 5 | l H |
| | 24 | 4 | l Le |
| - | 50 | OPEN | |
| | 25 | | ı |

| WIRING CH | | |
|-----------|--------|---------------|
| PORT NO. | TELCO | USOC |
| PURT NO. | 50 PIN | RJ-45, 2-WIRE |
| DODES | 26 | 5 |
| PORT 25 | 1 | 4 |
| | 27 | 5 |
| PORT 26 | 2 | 4 |
| PORT 27 | 28 | 5 |
| | 3 | 4 |
| PORT 28 | 29 | 5 |
| | 4 | 4 |
| | 30 | 5 |
| PORT 29 | 5 | |
| | 31 | <u>4</u> 5 |
| PORT 30 | 6 | |
| | 32 | <u>4</u> 5 |
| PORT 31 | | |
| | 7 | <u>4</u> 5 |
| PORT 32 | 33 | |
| | - 8 | <u>4</u> 5 |
| PORT 33 | 34 | 5 |
| FORT 33 | 9 | <u>4</u> 5 |
| PORT 34 | 35 | 5 |
| FURT 34 | 10 | <u>4</u> 5 |
| DODES | 36 | 5 |
| PORT 35 | 11 | 4 |
| | 37 | 5 |
| PORT 36 | 12 | 4 |
| | 38 | <u>4</u> 5 |
| PORT 37 | 13 | |
| | 39 | <u>4</u> 5 |
| PORT 38 | 14 | 4 |
| | 40 | 5 |
| PORT 39 | 15 | |
| | | <u>4</u> 5 |
| PORT 40 | 41 | |
| | 16 | 4 |
| PORT 41 | 42 | 5 |
| 1 01(1 41 | 17 | 4 |
| PORT 42 | 43 | 5 |
| FORT 42 | 18 | 4 |
| PORT 43 | 44 | 5 |
| PURI 43 | 19 | 4 |
| DODT 44 | 45 | 5 |
| PORT 44 | 20 | 4 |
| | 46 | 5 |
| PORT 45 | 21 | 4 |
| | 47 | 5 |
| PORT 46 | 22 | 4 |
| _ | 48 | 5 |
| PORT 47 | 23 | 4 |
| | 49 | 5 |
| PORT 48 | | |
| _ | 24 | 4 |
| - 1 | 50 | OPEN |
| | 25 | J. L.14 |

NOTE: UNLESS OTHERWISE SPECIFIED

1. MATERIAL:

A. 48-PORT PATCH PANEL: 16 GA CRS

B. JACK HOUSING: ABS, UL 94V-0

C. SPRING WIRE: SQUARE SPRING WIRE, TEMPERED PHOSPHOR BRONZE

D. GOLD RATING: 50 MICRO INCHES OF GOLD OVER 100 MICRO INCHES OF NICKEL

2. SURFACE FINISH: BLACK POWDER COAT

For warranty information, go online to icc.com/warranty.

Part No.: ICMPP48FT2

Rev: A Page 2 of 2 I 888-ASK-4ICC icc.com csr@icc.com

c.com I

Part No: ICMM48TF2

ree

Rev: A

© Copyright 2013, ICC. This document and the designs, specifications and information contained herein are the property of ICC. Reproduction, modification, alteration or unauthorized use without ICC's approval is strictly prohibited. ICC and the ICC logo are registered trade name and trademark of ICC. All rights reserved.